

- 6. emitted color: red
- 7. light source: LED
- 8. shell material: stainless steel
- 9. light source lifespan: ?200000h
- 10. surge protection grade: 3KA
- 11. rainproof: can be exposed to rain in any wind direction
- 12. radiation: can be exposed to solar radiation
- 13. seismic resistance: 10~500Hz, 2G, 10min /cycle, XYZ60 minutes for each axis
- 14. mean time between failure: ?200000h, MIL-HDBK-217F (25°C)
- 15. effective intensity: night 32,5cd
- 16. photocell stage: 50/100Lux
- 17. vertical divergence: >10°
- 18. horizontal output: 360°
- 19. overall size: 385*370*310 mm (L*W*H)
- 20. installation size: 80*80*M8 mm
- 21. battery power: 12V 14Ah
- 22. ambient temperature: -25°C ~ +65°C
- 23. weight: 6,5kg
- 24. wind load: 240 km/h
- 25. luminous mirror material: optical PC
- 26. protection grade: IP68
- 27. salt spray: can be exposed to salt spray
- 28. EMC standars: Emitted:EN55022 (CISPR22) class Aharmonic wave:EN6100-3-2-3)
- 29. altitude: ?5500m

Reviews

There are yet no reviews for this product.